

Improvement of Gasoline Octane Number by Using Organic Compounds

*Nibal H. AL-Mashhadani**
*Ayad A. Mohamed***
*Enaam M. Ali***
*Areej S. Mahmood**

*Muna M. Khudhair **
*Zaineb A. Al Kareem***
*Engam A. AL Mohsun **
*Mariam M. Jaseem**

Received 20, December, 2012

Accepted 5, February, 2014

Abstract:

The toxic lead additives to gasoline are no longer used in many countries around the world. Many other countries are now phasing out the lead in gasoline. Although the lead fuel is still in use in Iraq, several plans are considered to phase out the lead. The use of organic compounds to replace the lead additives in gasoline is considered now as an option in Iraqi refineries.

The main objective of this project was preparation of premium gasoline, by blending of gasoline with Alternative additives (alcohol, aromatic) to enhancing octane number of Al-Doura gasoline pool. Improved gasoline was tested by ASTM standard method which includes octane number measuring by CFR engine analyzer.

Gasoline pool RON (80) was used and selective components were added to the gasoline pool (1-3%) to improving it octane, such as ethanol, methanol, isopropanol, isobutanol, benzene, nitrobenzene, Aniline, and nitro aniline. Octane number of blends was measured by CFR engine. Mixture of alternative additives was prepared and adding in 1-3% vol to the gasoline pool.

It was found that the additives show significant improvement of octane number of gasoline but the important increasing of RON was shown on use mixture of alcohols and aniline.

Key words: gasoline, octane number, antiknock additive, CFR analyzer

Introduction:

Internal combustion engines produce moderately high pollution levels, due to incomplete combustion of carbonaceous fuel, leading to carbon monoxide and some soot along with oxides of nitrogen, sulfur and some unburnt hydrocarbons, depending on the operating conditions and the fuel/air ratio [1].

Gasoline is a complex mixture of hydrocarbons that normally boils below 355°F (180°C) or at the most, below 390°F (200°C). The hydrocarbon constituents in this range are those that have 4 to 12 carbon

atoms in their molecular structure. These hydrocarbons fall into three categories such as paraffins, olefins and aromatics [2]. Automotive gasoline has been classified into two grades, premium and regular on the basis of octane number. Gasoline with higher octane number has numerous benefits including reduced exhaust emissions [3] and engine noise, improved cold starting and engine durability. The key indication of performance property of gasoline under various engine conditions is its octane number (ON) which included : Research Octane Number (RON) and

*Ministry of Science & Technology, Directorate of Materials Research, Petroleum Research Centre.

*Ministry of Petroleum, Company of Middle Petroleum, Al Doura Refinery.

Motor Octane Number (MON). Finished gasoline must meet certain octane number specifications[4,5] .

Octane Number is defined as the volume percentage of iso octane in blend of normal heptane and iso octane , which produces the same knock intensity as the test fuel under standard test conditions in an ASTM internal combustion engine[5].

In the last 80 years ,the petrochemical methods for the production of fuels improved continuously to meet the demand both on the simultaneously growing amounts and the constantly increasing knock resistance of gasoline. Different additives were applied to achieve the required specifications of the highly knock resisting super grade gasolines used today . Selective components were used as antiknock agent to improve octane number of unleaded gasoline divided to many groups: metallic, alcohols, aromatics ,and others[6].

Historically ,lead has been an important source of increasing octane number. Because of the harmfulness of tetra ethyl lead ,its use has been forbidden in almost all countries[7] .

The addition of oxygenates to gasoline offers many advantages, among which: more complete combustion and reduction of carbon monoxide emission ,being a renewable energy source ,increased octane number ,and increased volatility. There are also disadvantages in adding oxygenates to gasoline among which includes: corrosion, lower energy content, increased cost, and increased volatility[8].

Alcohols are higher octane number than typical gasoline. They are more effective in low octane gasoline than in high octane gasoline. The behaviour of alcohols in mixed component as octane

improvers of gasoline was not known and the literature of this subject is few [9].

Thus ,the main objective of this research was to study the effect of the addition of aromatic and alcoholic compounds (each of them alone and together) to the gasoline fuel that produced in Al-Doura Refinery by measuring octane number by CFR engine.

Materials and Methods:

Table (1)Nomenclature

Symbol	Description
ASTM	American Society for Testing Material
RON	Research Octane Number
MON	Motor Octane Number
Sp.gr	Specific Gravity
RVP	Reid Vapor Pressure
Temp	Temperature
I.B.P	Initial Boiling Point
AKI	Antiknock Index
CFR	Cooperative Fuel Research
E.B.P	Ending Boiling Point

Materials

1- Gasoline

Gasoline were used and obtained from Al-Doura refinery which have properties and test methods are clearly defined in the table (2).

Table (2) Specification and Test Method of Al -Doura Commercial Gasoline

Properties Items	Test Methods	A-Doura Commercial Gasoline
Sp.gr.	IROX test	0.856
RVP bar	ASTM D323	6.5
Distillation	ASTM D86	
Temp C° I.B.P.		40
%10	43	62
%20	52	67
%30	58	75
%40	63	85
%50	68	98
%60	74	114
%70	80	129
%80	86	143
%90	97	167
E.B.P	115	219
Max.Soot content ppm	ASTM D4294	648.6
Water content ppm	ASTM D4928	133.09
Existent gum mgm/100ml	ASTM D381	3.4
Calorific value kcal/kgml	11488	11253
MON	ASTM D2700	80
RON	ASTM D2699	84
Aromatics vol%	IROX test	60.91
Olefins vol%	IROX test	0
Naphthenes vol%	IROX test	2.35
Paraffins vol%	IROX test	36.74

2- Absolute methanol, absolute ethanol, isopropanol, isobutanol, benzene, nitrobenzene, aniline, and m-nitroaniline of 99.95% purity were of analytical reagent grade and were obtained from SIGMA COMPANY.

Experimental procedure

1- First Stage

All selective components are added to the Al- Doura gasoline at different vol% as follow:

- 1- 300ml of gasoline was prepared at refrigerator temp. in glass container had fitting cover.
- 2- Octane number of gasoline was measured by CFR engine.
- 3-(1.5-6) ml of each component included (methanol, ethanol, isopropanol, isobutanol, benzene

,nitrobenzene, aniline) were taken by using pipette to blend with 300 ml of gasoline in glass container with shaking, and weight amount of m-nitroaniline and dissolved in solvent, next add to gasoline container.

4- Octane number of these blend were measured by CFR engine.

5-Repeat the 3 and 4 with another selective component.

2-Second Stage

Additives prepared from selective components which used at different vol% by blending components which appeared activity to enhancement octane preparation of pool like alcohols and aromatics in different vol%. All prepared additives were tested by added to prepare pool and measured octane number of the blends as follows:

1- 300 ml preparation gasoline must be prepared for measuring octane number by CFR engine.

2- (3-9)ml of prepared additives were taken by using pipette to blend with 300 ml of gasoline in glass container with shaking.

3-Octane number of blended gasoline is measured by CFR engine.

Analysis Method

Cooperative Fuel Research Engines (CFR) (D2699, D2700) was used to determine the octane number as follows:

1- The Research octane number RON of a spark-ignition engine fuel is determined using a standard test engine and operating conditions to compare its knock characteristic with those of PRF blends of known RON. Compression ratio and fuel-air ratio are adjusted to produce standard AKI for the sample fuel, as measured by a specific electronic detonation meter instrument system. A standard AKI. guide table relates CFR engine to RON level for this specific method. The fuel-air ratio

for the sample fuel and each of the primary reference fuel blends is adjusted to maximize AKI for each fuel.

2- The fuel-air ratio for maximum AKI. may be obtained:

a-By making incremental step changes in mixture strength, observing the equilibrium AKI value for each step, and then selecting the condition that maximizes the reading .

b-By picking the maximum AKI as the mixture strength is changed from either rich-to-lean or lean-to-rich at a constant rate (ASTM D2699 1989).

Results and Discussions

To find the optimum dosage of chemical components that enhance the octane number of the gasoline produced in Al-Doura Refinery, chemical components were used as in the different stages.

1- First Stage

It was been investigated that the effectiveness of different components in Al-Doura refinery gasoline. The following were used as the octane-increasing components in the studies:

1- Alcohols. 2- Aromatics Compounds. Selective components are added to the Al-Doura gasoline pool in various 0.5-3vol% and octane number is measured by CFR engine, as follows:

Alcohol components: Alcohols were used as antiknock agent to enhance octane value of unleaded gasoline. Alcohol components added to Al-Doura gasoline in various vol%, octane number was measured by CFR engine, and the results are listed in table(3).

Table (3) Octane Number of Al-Doura Refinery Unleaded Gasoline with Alcohol Components in Different vol%

Alcohol Components	Vol%				
	0	0.5	1	1.5	2
Methanol	80	82	82.5	83	83.5
Ethanol	80	80.5	81.1	81.6	82
Isopropanol	80	82.4	83.2	83.7	84
Isobutanol	80	81.5	82	82.5	83.5

Methanol, ethanol, isopropanol, and isobutanol in the amount of 0.5-2 vol% are used as octane booster. They are attractive because of their low cost in comparison to other components. On addition of 2 vol% alcohol components, the octane number of gasoline increased by 2-4 points. Isopropanol can thus be recommended as an octane booster for production of high octane unleaded gasoline. The oxygen ratio content in alcohol was an influence factor on RON of blended gasoline with alcohol components.

Aromatics Components: Selected aromatics components added to Al-Doura pool in various vol%, octane number was measured by CFR engine. From the result appears in table (4) it can be concluded that benzene and nitrobenzene had same effect for increasing octane value of blended Al-Doura refinery unleaded gasoline at the 2 vol%, while aromatic amine (aniline) in concentration at 2 vol% increasing the octane number by 7.5 points.

Table (4) Octane Number of Al-Doura Refinery Unleaded Gasoline with Aromatic Components

Aromatic Components	vol%				
	0	0.5	1	1.5	2
Benzene	80	80.6	81.2	82.1	83
Nitrobenzene	80	81.1	81.7	82.3	83
Aniline	80	82	84.2	86.1	87.5
Nitroaniline	80	81	81.2	81.2	81.2

For nitro compounds the proposed mechanism of ignition is free radical

,the nitro group cleave at space and time in the stratified injection spray such that the corresponding free radicals together with free radicals of fuel are sufficient to promote quicker ignition, the nitro group must cleave neither too early nor too late. In addition ,the aromatic ring should be free of groups that tend to stabilize the radical formed by the cleavage of the nitro group and thus aromatic rings are undesirable because of their ability to stabilize free radicals and delay the ignition[10]. As a result nitro aromatic compounds don't shown significant increasing octane number of gasoline.

2- Second stage

Optimum result may be obtained by using a mixture of alcohols. RON 84.2 was obtained from blending prepared unleaded gasoline with 2% vol preparation of components mixture which contain mixed alcohols and appear in table (5).

Table (5) Octane Number of Al-Doura Refinery Unleaded Gasoline with Preparation Alcohols Mixture

Vol %	RON	Increasing RON
0	80	0
0.5	81.6	1.6
1	82.2	2.2
1.5	82.7	2.7
2	84.2	4.2

Optimum result may be obtained by using a mixture of additives so as to ameliorate the deficiencies of each the additives. RON 89.3 was obtained from blending prepared unleaded gasoline with (1.5% mixed alcohols and 1.5 % aniline) components mixture; blended RON was measured by CFR engine. The results of blended RON for blending prepared component mixtures which contain (alcohols and aromatics) appear in table (6). These component mixture have the greatest

effect in gasoline than use each component alone.

Table (6) Octane Number of Al-Doura Refinery Unleaded Gasoline with Preparation Component Mixture (mixed alcohols & aniline)

Vol %	RON	Increasing RON
0	80	0
1	84.4	4.4
2	87.8	7.8
3	89.3	9.3

Conclusions:

Based on the previously discussed analyses, the following conclusions may be drawn:

- The experimental results of this project for RON measuring method showed fast, accuracy, and reliable analysis of gasoline.
- All selective chemical components act positively to improved octane number of Al- Doura gasoline.
- The Octane Booster of this project was Aniline, which was recorded the largest RON.
- Mixture of component was prepared from active selective components; include alcohol and aromatic compounds.
- The best preparation component mixture is better act with high octane gasoline than use each component alone.

Recommendations

There is still a need to generate data and experience by running tests and analyzing the environmental effects of blending gasoline. Thus the need to apply the precautionary principle to any gasoline blending component, and insist on a thorough evaluation of implications of such a decision. We must be much more certain of the toxicity, persistence and bioaccumulation of gasoline blending components, since it is given that these

chemicals will be used in large amounts throughout the world.

References:

- 1- Hamdan M.A., Al-Subaih T.A., (2002), "Improvement of locally produced gasoline and studying its effects on both the performance of the engine and the environment", 43,1811-1820 .
- 2- Schoonveld G. A. and Marshall W.F., (2008), "The Total Effect of a Reformulated Gasoline on Vehicle Emission by Technology", Pak. J. Anal. Environ. Chem. ,91 Vol. 9, No. 2, 61-66.
- 3- Brown S. S., Nomoto S. and Sunderman F. W.,(1999), Physics and Chemistry of Petroleum Products, Ranjan K. Bose (Ed.), Tate Energy Research Institute, Darbari Seth Block, New Delhi, India.
- 4- Knock Characteristics of Motor Fuels by the Research Method American Society for Testing and Materials Test Method D2699, American Society for Testing and Materials: West Conshohocken, PA, 1989, p.1-68.
- 5- Knock Characteristics of Motor Fuels by the Motor Method American Society for Testing and Materials Test Method D2700, American Society for Testing and Materials: West Conshohocken, PA, 1989, p.1-68.
- 6- Albahri T. A. , Riazi M. R. , and Alqattan A. A.,(2002), "Octane Number and Aniline Point of Petroleum Fuels", Fuel Chemistry Division Preprints , 47(2), 710.
- 7- Caldwell J., (2000), " Environmental Protection Agency", Toxicology and Industrial Health,14(3);429-454.
- 8- Thomas V.M., (1995), "The elimination of lead in gasoline", Annual Review of Energy and Environment ,20, 301-324.
- 9- Butkus A., Pukalskas S.,(2004), " The Research into the Influence of Ecological Petrol Additives in the Automobile Laboratory", Transport,11(2),80-82.
- 10- Galen J.S. and Mohanprasad A.D.,(2003), "Synthesis and Evaluation of Alkyl Nitrates from Triglycerides as Cetane Improvers", Ind. Eng. Chem. Res., 42,5042-5053.

تحسين العدد الاوكتاني للказولين باستخدام مركبات عضوية مختلفة

نبال حاتم رشيد* منى محمود خضير* اياد احمد محمد** زينب عبد الكريم عون**
 انعام محمد علي** انعام عبد المحسن عبد السادة* اريج شاكر محمود*
 مريم محمد جاسم*

* وزارة العلوم والتكنولوجيا / دائرة بحوث المواد / مركز بحوث النفط
 **وزارة النفط /مصفى الدورة / شركة نفط الوسط

الخلاصة:

لقد تم الاستغناء عن استعمال مركبات الرصاص السامة كمضافات رئيسية إلى الكازولين في العديد من بلدان العالم غير إن هنالك بعض الدول مازالت لحد الآن تستعمله والعراق من بين هذه الدول. إلا انه وضعت خطط عديدة للاستغناء عن استخدامه واستعمال المركبات العضوية كبديل للإضافات الرئيسية في الكازولين في المصافي العراقية.

ويهدف البحث الحالي إلى دراسة تأثير المركبات العضوية الأكثر شيوعاً على تحسين العدد الأوكتاني للказولين في مصفى الدورة وكذلك في تحضير الكازولين بمزجه مع بعض المضافات الإنتقائية الكحولات، المركبات الأروماتية (وقياس العدد الأوكتاني للказولين بطريقة محلل المحرك القياسية).

لقد تم استخدام الكازولين ذو العدد الأوكتاني 80 كأساس وتمت إضافة الكحولات مثل الميثانول والايثانول والايسوبروبانول والايسوبوتانول والمركبات الأروماتية مثل البنزين والنتروبنزين والانيلين والنتروانيولين بنسب تتراوح من (0.5-2)% وتم استخدام مزيج من المضافات الكحولات والانيولين (بنسب 1-3%) وقياس العدد الأوكتاني للبنزين المحسن.

وقد وجد ان استخدام المضافات عملت على رفع العدد الاوكتاني بنسبة لا بأس بها ولكن الزيادة الواضحة كانت باستخدام 3% من مزيج الكحولات والانيولين.